




减压阀/Pressure Regulator AR1000-5000 系列/Series



符号/Symbol

规格/Specification

保证耐压力/Ensured Pressure Resistance	1.5MPa(15kgf/cm ²)
最高使用压力/Highest Working Pressure	1.0MPa(10kgf/cm ²)
调压范围/Pressure Regulating Range	AR1000:0.05-0.7MPa(0.5-7kgf/cm ²) AR2000-5000:0.05-0.85MPa(0.5-8.5kgf/cm ²)
环境及流体温度/Ambient and Fluid Temperature	5-60°C
阀型/Valve Type	带溢流性/With Overflow

*还有调压范围/Pressure Regulating Range : 0.02-0.2MPa(0.2-2kgf/cm²)

型号 Model	规格/Specifications				配件/Accessories	
	*额定流量 /Rated Flow (L/min)	**接管口径 /Port Size (G)	压力表口径 /Pressure Gauge Size(G)	重量 /Weight (kg)	托架 /Bracket	压力表 /Pressure Gauge
AR1000-M5	100	M5	1/16	0.08	B120	G27-10-R1
AR2000-01	550	1/8	1/8	0.27	B220	G36-10-01
AR2000-02		1/4				
AR2500-02	2000	1/4	1/8	0.27	B220	G36-10-01
AR2500-03		3/8				
AR3000-02	2500	1/4	1/8	0.41	B320.	
AR3000-03		3/8				
AR4000-03	6000	3/8	1/4	0.84	B420	G46-10-02
AR4000-04		1/2				
AR4000-06	6000	3/4	1/4	0.94		
AR5000-06	8000	3/4	1/4	1.19		
AR5000-10		1				

注： *供应压力为0.7MPa(7.1kgf/cm²)设定压力为0.5MPa(5.1kgf/cm²)的情况下

*Under the circumstance that the supply pressure is 0.7MPa(7.1kgf/cm²) and set pressure is 0.5MPa(5.1kgf/cm²)

**接管口径另有Rc,NPT螺纹可供选择

Rc and NPT port size are available