




空气过滤组合(三联件)/Air Filter Combination(Three Elements)

HNAC2000-5000 系列/Series



符号/Symbol

规格/Specification

保证耐压力/Ensured Pressure Resistance	1.5MPa(15kgf/cm ²)
最高使用压力/Highest Working Pressure	1.0MPa(10kgf/cm ²)
环境及流体温度/Ambient and Fluid Temperature	5-60°C
*过滤精度/*Filter Precision	25μm
建议用油/Recommended Oil Use	透平1号油/Turbine No.1 Oil ISOVG32
容器材料/Container Material	铝压铸件/Aluminum Die Casting
调压范围/Pressure Regulating Range	0.05-0.85MPa(0.5-8.5kgf/cm ²)
阀型/Valve Type	带溢流性/With Overflow

*还有5,50μm可供选择/*5,50μm available in addition

型号 Model	规格/Specifications							配件/Accessories	
	组件/Assembly			*额定流量 /Rated Flow (L/min)	**接管口径 /Port Size (G)	压力表口径 /Pressure Gauge Size	重量 /Weight (kg)	托架 /Bracket (2个)	压力表 /Pressure Gauge
	过滤器 /Filter	减压阀 /Regulator	油雾器 /Mist Seperator						
HNAC2000-01M	HNAF2000	AR2000	HNAL2000	500	1/8	1/8	0.74	Y20L	G36-10-01
HNAC2000-02M					1/4				
HNAC2500-02M	HNAF3000	AR2500	HNAL3000	1500	1/4	1/8	1.04	Y30L	
HNAC2500-03M					3/8				
HNAC3000-02M	HNAF3000	AR3000	HNAL3000	2000	1/4	1/8	1.18	Y30L	
HNAC3000-03M					3/8				
HNAC4000-03M	HNAF4000	AR4000	HNAL4000	4500	3/8	1/4	2.14	Y40L	G46-10-02
HNAC4000-04M					1/2				
HNAC4000-06M	HNAF4000-06M	AR4000-06	HNAL4000-06M	4500	3/4	1/4	2.47	Y50L	
HNAC5000-06M	HNAF5000	AR5000	HNAL5000	5000	3/4	1/4	3.82	Y60L	
HNAC5000-10M					1				

*供应压力为0.7MPa(7.1kgf/cm²)设定压力为0.5MPa(5.1kgf/cm²)的情况下

*Under the circumstance that the supply pressure is 0.7MPa(7.1kgf/cm²) and set pressure is 0.5MPa(5.1kgf/cm²)

**接管口径另有Rc,NPT螺纹可供选择

Rc and NPT port size are available