



HAND VALVES

(FOR MALAYSIA REFERENCES ONLY)

CONSTRUCTION		FEATURES	SPECIFICATIONS	CODE DESIGNATION		
				MODEL	TUBE SIZE	THREAD SIZE
		<ul style="list-style-type: none"> Turning the knob to shut off pressure completely Three way directional control configuration releases the residual internal pressure on the output side when manually closed Ideal for inspecting or repairing any devices without compromising the safety 	Application Fluid Type : Air, Vacuum Working Pressure Range : 0~10.2kgf/cm ² Negative Pressure : -750mmHg Operating Temperature : 0 ~ 60° C Tube Material : Nylon & Polyurethane	HVFF	08	02
					04 - 4mm	01 - R1/8
					06 - 6mm	02 - R1/4
					08 - 8mm	03 - R3/8
					10 - 10mm	04 - R1/2
					12 - 12mm	
					14 - 14mm	
					16 - 16mm	

Type & Sizing	Remarks
	06-06
	08-06
	08-08
	10-08
	10-10
	12-10
	12-12

Type & Sizing	Remarks
	01-01
	02-01
	02-02
	03-02
	03-03
	04-03
	04-04

Type & Sizing	Remarks
	06-01
	06-02
	06-03
	06-04
	08-01
	08-02
	08-03
	08-04
	10-01
	10-02
	10-03
	10-04
	12-01
	12-02
	12-03
	12-04