



PUSH-IN FITTING

(FOR MALAYSIA REFERENCES ONLY)

CONSTRUCTION	FEATURES	SPECIFICATIONS	CODE DESIGNATION		
			MODEL	TUBE SIZE	THREAD SIZE
			PC	8	02

	- One Touch push to connect configuration allow an instant tubing connection - Nickel-plated metallic feature ensure anti-corrosion and anti-contamination - Pre-applied sealant on all external thread eliminates the additional sealing requirement. - Tightening by external flat to flat hexagonal or internal configurations by using allen key.	Medium : Air, Vacuum Operating Pressure : 0 ~ 10 bar Negative Pressure : -750mmHg ~ 0 Operating Temperature : 0 ~ 60° C Tube Material : Polyurethane			
				4 - 4mm	01 - R1/8"
				6 - 6mm	02 - R1/4"
				8 - 8mm	03 - R3/8"
				10 - 10mm	04 - R1/2"
				12 - 12mm	

Type & Sizing	Remarks
	4-01
	4-02
	6-01
	6-02
	6-03
	6-04
	8-01
	8-02
	8-03
	8-04
	10-01
	10-02
	10-03
	10-04
	12-01
	12-02
	12-03
	12-04
	4-M5
	6-M5
	4-01
	4-02
	6-01
	6-02
	6-03
	6-04
	8-01
	8-02
	8-03
	8-04
	10-01
	10-02
	10-03
	10-04
	6-04
	8-04
	8-06
	10-06
	10-08
	12-06
	12-08
	12-10

Type & Sizing	Remarks
	6-01
	6-02
	6-03
	6-04
	8-01
	8-02
	8-03
	8-04
	10-01
	10-02
	10-03
	10-04
	12-01
	12-02
	12-03
	12-04
	6-01
	6-02
	6-03
	6-04
	8-01
	8-02
	8-03
	8-04
	10-01
	10-02
	4
	6
	8
	10
	12
	6-04
	8-06
	10-08
	12-10
	6-04
	8-04
	8-06
	10-06
	10-08
	12-08
	12-10

Type & Sizing	Remarks
	6-01
	6-02
	6-03
	6-04
	8-01
	8-02
	8-03
	8-04
	10-01
	10-02
	10-03
	10-04
	4
	6
	8
	10
	12
	6-04
	8-04
	8-06
	10-06
	4-M5
	6-M5
	4-01
	4-02
	6-01
	6-02
	6-03
	6-04
	8-01
	8-02
	8-03
	8-04
	10-01
	10-02
	10-03
	10-04
	12-01
	12-02
	12-03
	12-04
	4
	6
	8
	10
	12

Type & Sizing	Remarks
	4
	6
	8
	10
	12
	4
	6
	8
	10
	4
	6
	8
	10
	6-04
	8-04
	8-06
	10-06
	10-08
	12-08
	12-10
	6-04
	8-04
	8-06
	10-06
	10-08
	12-08
	12-10
	6-01
	6-02
	6-03
	6-04
	8-01
	8-02
	8-03
	8-04
	10-01
	10-02
	10-03
	10-04
	12-01
	12-02
	12-03
	12-04
	4
	6
	8
	10
	12



PUSH-IN FITTING

(FOR MALAYSIA REFERENCES ONLY)

Type & Sizing		Remarks
PM 	4	
	6	
	8	
	10	
	12	
POH 	1	
	2	
	3	
	4	
	6	
	M5	